

Corner originally set as a post in 1821 by Wm. B. Laughlin with the following witnesses: 10" beech bearing north 15 degrees, and a 12" sugar bearing east 22 links. (M. C. Atlas p. 16) No records were found indicating a stone or witnesses. Corner referenced by Fortner on 5/21/75 and called a R.R. spike with cut x. Corner referenced by Cleveland on 6/15/82 and called a brass plug with plate. Corner referenced by Wilcoxen on 10/12/84 and called a brass plug with plate. Corner referenced by Wilcoxen on 10/06/99and called a brass plug with plate. Corner was excavated on 9/19/02 and a brass plug with plate was found 6" down. No stone was found. A #205 cast iron Harrison Monument was set in position as the corner.

| | 1705150 | 6 | |
|------|----------|-----------------------------------|-------|
| REF. | DISTANCE | DESCRIPTION | |
| 1. | 18.45 | Mag nail w/bw SF PwP no # 8"up | |
| 2. | 88.22' | Mag nail w/bw NW PwP no # 48" up | |
| 3. | 22.29' | Mag nail w/bw S fence post 30" up | |
| 4. | 98.63' | PK nail W PwP # 417-221 HA 12"up | Alte. |
| 5. | 137.06' | PK nail F PwP#108-181HB 12"up | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |